

SPECIFICATION OF BSFQ□□□□CDKC SERIES

AEC-Q200



FEATURES

1. High saturation current inductor with ferrite core and magnetic shielding design.
2. Low profile : Surface mounting(SMT) type and thickness with 2.0 to 5.0 mm for different size.
3. Low loss realized with low DCR.
4. Compatible with Pb-free RoHS and AEC-Q200.

APPLICATIONS

1. Automotive application



ORDERING CODE



BSFQ0318CDKC 4R7 M T
(1) (2) (3)(4)

(1) PRODUCT TYPE CODE AND SIZE CODE

(2) INDUCTANCE

(3) INDUCTANCE TOLERANCE (K : $\pm 10\%$, M : $\pm 20\%$)

(4) REEL TAPING



SHAPE & DIMENSIONS

UNIT:mm

SIZE CODE	A	B	C	D Typ.	E	F	G		
BSFQ0318CDKC	3.0 $\pm$ 0.3	1.9(max)	3.5 $\pm$ 0.3	1.2	3.5	1.60	0.8		
BSFQ0302CDKC	3.0 $\pm$ 0.3	2.3(max)	3.5 $\pm$ 0.3	1.2	3.5	1.60	0.8		
BSFQ0402CDKC	4.0 $\pm$ 0.3	2.2 $\pm$ 0.3	4.5 $\pm$ 0.3	1.5	4.5	2.10	0.8		
BSFQ0403CDKC	4.0 $\pm$ 0.3	3.2 $\pm$ 0.3	4.5 $\pm$ 0.3	1.5	4.5	2.10	0.8		
BSFQ0502CDKC	5.2 $\pm$ 0.3	2.5 $\pm$ 0.3	5.8 $\pm$ 0.3	2.0	5.5	2.25	1.5		
BSFQ0503CDKC	5.2 $\pm$ 0.3	3.0 $\pm$ 0.3	5.8 $\pm$ 0.3	2.0	5.5	2.25	1.5		
BSFQ0504CDKC	5.2 $\pm$ 0.3	4.5 $\pm$ 0.3	5.8 $\pm$ 0.3	2.0	5.5	2.25	1.5		
BSFQ0703CDKC	7.0 $\pm$ 0.3	3.5 $\pm$ 0.3	7.8 $\pm$ 0.3	2.5	7.5	3.05	1.9		
BSFQ0705CDKC	7.0 $\pm$ 0.3	5.0 $\pm$ 0.3	7.8 $\pm$ 0.3	2.5	7.5	3.05	1.9		
BSFQ1004CDKC	9.0 $\pm$ 0.3	4.0 $\pm$ 0.3	10.0 $\pm$ 0.3	2.9	9.5	3.65	2.5		
BSFQ1005CDKC	9.0 $\pm$ 0.3	5.4 $\pm$ 0.3	10.0 $\pm$ 0.3	2.9	9.5	3.65	2.5		
BSFQ1006CDKC	9.0 $\pm$ 0.3	6.8 $\pm$ 0.3	10.0 $\pm$ 0.3	2.9	9.5	3.65	2.5		

※All the data listed in this catalogue are for reference only, King Core reserves the right to alter or revise the specifications without prior notification.











KING CORE ELECTRONICS INC.
Tel:886-3-4698855 Fax:886-3-4691395

No.269,Nanfong Rd.,Pingjhen City,Taoyuan County, Taiwan
E-mail:kc@mail.kingcore.com.tw Web Site:http://www.kingcore.com.tw

SMD POWER INDUCTORS → BSFQ0318CDKC SERIES

ELECTRICAL CHARACTERISTIC

ORDERING CODE	Inductance (μH)	DC Resistance ($\text{m}\Omega$)max	SRF (MHz)min	Isat (A)max	IDC (A)max
BSFQ0318CDKC1R0MT	1.0	58	85	3.80	2.40
BSFQ0318CDKC2R2MT	2.2	115	45	2.60	1.90
BSFQ0318CDKC3R3MT	3.3	155	40	2.20	1.70
BSFQ0318CDKC4R7MT	4.7	200	35	1.90	1.35
BSFQ0318CDKC100MT	10	520	20	1.20	0.82
BSFQ0318CDKC220MT	22	950	15	0.85	0.68
BSFQ0318CDKC330MT	33	1500	10	0.70	0.60
BSFQ0318CDKC470MT	47	1800	10	0.65	0.50



Test Freq.:100KHz/0.1V

Tolerance: K $\pm$ 10%,M $\pm$ 20%

※Isat:Based on Inductance decrease 30%

※IDC:Based on Temperature increase 40°C

※Operating temperature range : -40 to +125°C (including self-generated heat)

※All the data listed in this catalogue are for reference only, King Core reserves the right to alter or revise the specifications without prior notification.



KING CORE ELECTRONICS INC.
Tel:886-3-4698855 Fax:886-3-4691395

No.269,Nanfong Rd.,Pingjhen City,Taoyuan County, Taiwan
E-mail:kc@mail.kingcore.com.tw Web Site:http://www.kingcore.com.tw