

SPECIFICATION OF BSF□□□BNRM SERIES


FEATURES

1. Low profile construction and miniature size.
2. Magnetic shielded construction.
3. High current saturation.
4. For new generation portable product D/D converter unit.



APPLICATIONS

DVD、DSC、PDA、LCD display、
Smart phones、HDD、etc.



ORDERING CODE

BSF6030BNRM 2R2 M T
(1) (2) (3)(4)

- (1) PRODUCT TYPE CODE AND SIZE CODE
(2) INDUCTANCE
(3) INDUCTANCE TOLERANCE (M : $\pm 20\%$, N : $\pm 30\%$)
(4) REEL TAPING




FIG 1

FIG 2

FIG 3

FIG 4

SHAPE & DIMENSIONS

SIZE CODE	A mm	B mm	C mm	D mm	E mm	H	I	J	FIG	
BSF2010BNRM	2.0 $\pm$ 0.2	1.6 $\pm$ 0.2	1.05max	0.6 $\pm$ 0.2	—	1.10	1.00	0.90	1	
BSF2512BNRM	2.5 $\pm$ 0.2	2.1 $\pm$ 0.2	1.25max	0.85 $\pm$ 0.20	—	1.40	0.95	0.90	1	
BSF3010BNRM	3.0 $\pm$ 0.2	3.0 $\pm$ 0.2	1.05max	0.9 $\pm$ 0.2	—	2.90	1.00	1.20	2	
BSF3012BNRM	3.0 $\pm$ 0.2	3.0 $\pm$ 0.2	1.25max	0.9 $\pm$ 0.2	—	2.90	1.00	1.20	2	
BSF3015BNRM	3.0 $\pm$ 0.2	3.0 $\pm$ 0.2	1.55max	0.9 $\pm$ 0.2	—	2.90	1.00	1.20	2	
BSF5040BNRM	5.4 $\pm$ 0.2	5.7 $\pm$ 0.2	4.0 $\pm$ 0.2	1.5 $\pm$ 0.3	4.5 $\pm$ 0.3	6.10	3.07	3.05	4	
BSF6030BNRM	6.0 $\pm$ 0.2	6.0 $\pm$ 0.2	3.0 $\pm$ 0.2	1.9 $\pm$ 0.3	—	5.70	2.00	2.00	3	

※All the data listed in this catalogue are for reference only, King Core reserves the right to alter or revise the specifications without prior notification.












KING CORE ELECTRONICS INC.
Tel:886-3-4698855 Fax:886-3-4691395

No.269,Nanfong Rd.,Pingjhen City,Taoyuan County, Taiwan
E-mail:kc@mail.kingcore.com.tw Web Site:http://www.kingcore.com.tw

SMD POWER INDUCTORS → BSF6030BNRM SERIES

ELECTRICAL CHARACTERISTIC

ORDERING CODE	Inductance (μH)	DC Resistance ($\text{m}\Omega$)max	SRF(MHz) min	Isat (A)Typ	IDC (A)Typ
BSF6030BNRM2R2MT	2.20	27	20	10.3	7.20
BSF6030BNRM3R3MT	3.30	35	20	9.00	6.80
BSF6030BNRM4R7MT	4.70	45	15	7.20	6.60
BSF6030BNRM6R8MT	6.80	65	13	6.40	4.60
BSF6030BNRM100MT	10.0	82	7	4.80	4.10
BSF6030BNRM150MT	15.0	150	7	4.00	3.00
BSF6030BNRM220MT	22.0	170	5	3.20	2.90
BSF6030BNRM330MT	33.0	250	2.5	2.60	2.60
BSF6030BNRM470MT	47.0	360	2.5	2.30	1.80



※Test Frequency: 100KHz/1V

※Tolerance: M $\pm$ 20%

※Isat:Based on Inductance decrease 30%

※IDC:Based on Temperature increase 40°C

※Operating temperature range : -40 to +125°C (including self-heating)

※Storage Temp. : -40°C TO+85°C

※All the data listed in this catalogue are for reference only, King Core reserves the right to alter or revise the specifications without prior notification.



KING CORE ELECTRONICS INC.
Tel:886-3-4698855 Fax:886-3-4691395

No.269,Nanfong Rd.,Pingjhen City,Taoyuan County, Taiwan
E-mail:kc@mail.kingcore.com.tw Web Site:http://www.kingcore.com.tw