

# SPECIFICATION OF BSF□□□□CDKC ,CRKC SERIES

## FEATURES

1. High saturation current inductor with ferrite core and magnetic shielding design.
2. Low profile : Surface mounting(SMT) type and thickness with 2.0 to 5.0 mm for different size.
3. Low loss realized with low DCR.
4. Halogen free, lead free, RoHS compliant



## APPLICATIONS

1. D/D converter unit design for 3C products, VRM for server.
2. DVD, HDD, STB, LCD display, IP CAM, GPS, USB connector, Smart phones, Face Recognition System, IoT application...etc

## ORDERING CODE



BSF0403CRKC 100 M T  
 (1) (2) (3) (4)

(1) PRODUCT TYPE CODE AND SIZE CODE(CRKC with lower resistance and CDKC with high saturation current design)

(2) INDUCTANCE

(3) INDUCTANCE TOLERANCE ( K : ±10%, M : ±20% )

(4) REEL TAPING



## SHAPE & DIMENSIONS

UNIT:mm

SIZE CODE	A	B	C	D Typ.	E	F	G		
BSF0318CDKC	3.0±0.3	1.9(max)	3.5±0.3	1.2	3.5	1.60	0.8		
BSF0302CDKC	3.0±0.3	2.3(max)	3.5±0.3	1.2	3.5	1.60	0.8		
BSF0302CRKC	3.0±0.3	2.3(max)	3.5±0.3	1.2	3.5	1.60	0.8		
BSF0402CDKC	4.0±0.3	2.2±0.3	4.5±0.3	1.5	4.5	2.10	0.8		
BSF0402CRKC	4.0±0.3	2.2±0.3	4.5±0.3	1.5	4.5	2.10	0.8		
BSF0403CDKC	4.0±0.3	3.2±0.3	4.5±0.3	1.5	4.5	2.10	0.8		
BSF0403CRKC	4.0±0.3	3.2±0.3	4.5±0.3	1.5	4.5	2.10	0.8		
BSF0502CDKC	5.2±0.3	2.5±0.3	5.8±0.3	2.0	5.5	2.25	1.5		
BSF0503CDKC	5.2±0.3	3.0±0.3	5.8±0.3	2.0	5.5	2.25	1.5		
BSF0504CDKC	5.2±0.3	4.5±0.3	5.8±0.3	2.0	5.5	2.25	1.5		
BSF0504CRKC	5.2±0.3	4.5±0.3	5.8±0.3	2.0	5.5	2.25	1.5		
BSF0703CDKC	7.0±0.3	3.5±0.3	7.8±0.3	2.5	7.5	3.05	1.9		
BSF0705CDKC	7.0±0.3	5.0±0.3	7.8±0.3	2.5	7.5	3.05	1.9		
BSF0705CRKC	7.0±0.3	5.0±0.3	7.8±0.3	2.5	7.5	3.05	1.9		





※All the data listed in this catalogue are for reference only, King Core reserves the right to alter or revise the specifications without prior notification.



# SMD POWER INDUCTORS → BSF0403CRKC SERIES

## ELECTRICAL CHARACTERISTIC

ORDERING CODE	Inductance ( $\mu\text{H}$ )	DC Resistance ( $\text{m}\Omega$ )max	SRF (MHz)min	Isat (A)max	IDC (A)max
BSF0403CRKC100MT	10	85	15	1.20	1.80
BSF0403CRKC120MT	12	110	13	1.20	1.70
BSF0403CRKC220MT	22	180	10	0.85	1.50
BSF0403CRKC470MT	47	350	7	0.60	1.10



Test Freq.: 100KHz/1V

Tolerance: K $\pm$ 10%, M $\pm$ 20%

※Isat: Based on Inductance decrease 30%

※IDC: Based on Temperature increase 40 $^{\circ}\text{C}$

※Operating temperature range : -40 to +125 $^{\circ}\text{C}$  (including self-generated heat)

※All the data listed in this catalogue are for reference only, King Core reserves the right to alter or revise the specifications without prior notification.