

KC006 WCM SERIES

COMMON MODE CHOKE WIRING TYPE → WCM Series				Standard Type	
ORDERING CODE	Impedance (Ω)	Tol ±	Test Frequency (MHz)	DC Resistance (Ω)max	Rated Current (mA)max
WCM-2012-670T	67	25%	100	0.25	400
WCM-2012-900T	90	25%	100	0.30	400
WCM-2012-121T	120	25%	100	0.30	370
WCM-2012-161T	160	25%	100	0.35	350
WCM-2012-181T	180	25%	100	0.35	330
WCM-2012-221T	220	25%	100	0.40	300
WCM-2012-261T	260	25%	100	0.40	300
WCM-2012-371T	370	25%	100	0.45	280
WCM-2012HDMI-900T	90	25%	100	0.30	400

  

COMMON MODE CHOKE WIRING TYPE → WCM Series				Standard Type	
ORDERING CODE	Impedance (Ω)	Tol ±	Test Frequency (MHz)	DC Resistance (Ω)max	Rated Current (mA)max
WCM-3216-900T	90	25%	100	0.30	400
WCM-3216-161T	160	25%	100	0.40	350
WCM-3216-221T	220	25%	100	0.45	300
WCM-3216-261T	260	25%	100	0.50	310
WCM-3216-601T	600	25%	100	0.80	260
WCM-3216-102T	1000	25%	100	1.00	250
WCM-3216-222T	2200	25%	100	1.20	200

  

COMMON MODE CHOKE WIRING TYPE → WCM Series				Standard Type	
ORDERING CODE	Impedance (Ω)	Tol ±	Test Frequency (MHz)	DC Resistance (Ω)max	Rated Current (mA)max
WCM-1210HS-250T	25	25%	100	0.25	420
WCM-1210HS-600T	60	25%	100	0.25	400
WCM-1210HS-900T	90	25%	100	0.30	400
WCM-2012HS-120T	12	25%	100	0.20	450
WCM-2012HS-240T	24	25%	100	0.25	420
WCM-2012HS-320T	32	25%	100	0.25	400
WCM-2012HS-670T	67	25%	100	0.25	400
WCM-2012HS-900T	90	25%	100	0.30	400

  

COMMON MODE CHOKE WIRING TYPE → WCM Series				Standard Type	
ORDERING CODE	Impedance (Ω)	Tol ±	Test Frequency (MHz)	DC Resistance (Ω)max	Rated Current (mA)max
WCM-160808-100T	10	25%	100	0.30	500
WCM-160808-200T	20	25%	100	0.40	400
WCM-160808-300T	30	25%	100	0.45	350
WCM-160808-670T	67	25%	100	0.50	300
WCM-160808-900T	90	25%	100	0.55	250